



Powerware

Powerware® Basic ePDU™

Product Focus



Designed for reliable and cost effective power distribution Powerware basic ePDUs have the form factor and receptacle choices to meet the needs of demanding data center architects. With power levels ranging from 1.4kW all the way to 10kW, the ePDU has the right product for any application.

Features

- **High-density, high amperage receptacles** support blade servers and network switches
- **Satellite units** support servers and ancillary equipment
- **Clearly labeled circuits** simplify load balancing
- **Power cord retention bracket** improves power connectivity and reliability
- **Rotatable rackmount brackets** permit side mounting, improving installation flexibility
- **High-grade components** increases product reliability and fault-tolerance
- **Soldered or mechanical connections** increases product fault-tolerance and MTBF

Technical specifications

Part number	Inventory*	Description	Max kW	Input plug	Function	Cord	Orientation	Receptacles	Dimensions W H D		
Vertical mount 0U models											
PW101BA0U011	2	PW ePDU 1.4kW 5-15 input and 5-15 (8)output	1.44	5-15	BA	15'	0U	5-15 (8)	2.1	14	1.3
PW101BA0U012	2	PW ePDU 1.4kW 5-15 input and 5-15 (4)output	1.44	5-15	BA	15'	0U	5-15 (4)	2.1	24	1.3
PW101BA0U013	2	PW ePDU 1.4kW 5-15 input and 5-20 (6)output	1.44	5-15	BA	15'	0U	5-20 (6)	2.1	30	1.3
PW101BA0U014	2	PW ePDU 1.4kW 5-15 input and 5-20 (8)output	1.44	5-15	BA	15'	0U	5-20 (8)	2.1	48	1.3
PW102BA0U015	2	PW ePDU 1.9kW 5-20 input and 5-20 (8)output	1.92	5-20	BA	15'	0U	5-20 (8)	2.1	48	1.3
PW102BA0U016	2	PW ePDU 1.9kW 5-20 input and 5-20 (12)output	1.92	5-20	BA	15'	0U	5-20 (12)	2.1	72	1.3
PW102BA0U017	2	PW ePDU 1.9kW 5-20 input and 5-20 (8)output	1.92	5-20	BA	15'	0U	5-20 (8)	2.1	16	1.3
PW102BA0U019	2	PW ePDU 1.9kW 5-20 input and 5-20 (12)output	1.92	5-20	BA	15'	0U	5-20 (12)	2.1	60	1.3
PW102BA0U020	2	PW ePDU 1.9kW 5-20 input and 5-20 (10)output	1.92	5-20	BA	15'	0U	5-20 (10)	2.1	24	1.3
PW102BA0U018	2	PW ePDU 1.9kW L5-20 input and 5-20 (12)output	1.92	L5-20	BA	15'	0U	5-20 (12)	2.1	60	1.3
PW102BA0U021	1	PW ePDU 1.9kW L5-20 input and 5-20 (24)output	1.92	L5-20	BA	15'	0U	5-20 (24)	2.1	60	1.3
PW102BA0U022	2	PW ePDU 1.9kW L5-20 input and 5-20 (8)output	1.92	L5-20	BA	15'	0U	5-20 (8)	2.1	16	1.3
PW102BA0U023	2	PW ePDU 1.9kW L5-20 input and 5-20 (10)output	1.92	L5-20	BA	15'	0U	5-20 (10)	2.1	24	1.3
PW103BA0U032	2	PW ePDU 2.9kW L5-30 input and 5-20 (24)output	2.88	L5-30	BA	15'	0U	5-20 (24)	2.1	60	1.3
PW103BA0U038	2	PW ePDU 3.3kW IEC320-C20 input and IEC320-C13 (8)output	3.33	IEC320-C20	BA	6'	0U	IEC320-C13 (8)	1.6	16	1.6
PW103BA0U039	3	PW ePDU 3.3kW L6-20 input and IEC320-C13 (10)output	3.33	L6-20	BA	10'	0U	IEC320-C13 (10)	2.3	14	2
PW103BA0U120	3	PW ePDU 3.3kW L6-20 input and IEC320-C13 (24)output	3.33	L6-20	BA	10'	0U	IEC320-C13 (24)	2.3	29	2
PW103BA0U123	3	PW ePDU 3.3kW L6-20 input and IEC320-C13 (16)output	3.33	L6-20	BA	10'	0U	IEC320-C13 (16)	2.3	21	2
PW104BA0U042	2	PW ePDU 3.8kW 2 x L5-20 input and 5-20 (2 x 12)output	3.84	2 x L5-20	BA	15'	0U	5-20 (2 x 12)	2.1	60	1.3
PW105BA0U055	3	PW ePDU 5kW L6-30 input and IEC320-C19 (4), IEC320-C13 (24)output	4.99	L6-30	BA	10'	0U	IEC320-C19 (4), IEC320-C13 (24)	2.3	60	2
PW105BA0U056	1	PW ePDU 5kW L6-30 input and IEC320-C13 (24)output	4.99	L6-30	BA	10'	0U	IEC320-C13 (24)	1.75	64	1.9

Technical specifications (cont.)

Part number	Inventory*	Description	Max kW	Input plug	Function	Cord	Orientation	Receptacles	Dimensions		
									W	H	D
PW106BA0U064	3	PW ePDU 5.8kW 2 x L5-30 input and 5-15 (2 x 20)output	5.76	2 x L5-30	BA	10'	0U	5-15 (2 x 20)	3.2	64	1.9
PW306BA0U066	3	PW ePDU 5.8kW L21-20 input and IEC320-C19 (9), IEC320-C13 (36)output	5.76	L21-20	BA	10'	0U	IEC320-C19 (9), IEC320-C13 (36)	2.3	68	2.0
PW306BA0U067	3	PW ePDU 5.8kW L21-20 input and 5-20 (36)output	5.76	L21-20	BA	10'	0U	5-20 (36)	2.3	68	2.0
PW306BA0U068	3	PW ePDU 5.8kW L21-20 input and IEC320-C19 (3), IEC320-C13 (24), 5-20(6)output	5.76	L21-20	BA	10'	0U	IEC320-C19 (3), IEC320-C13 (24), 5-20(6)	2.3	68	2.0
PW306BA0U069	3	PW ePDU 5.8kW L21-20 input and 5-20 (24), L6-20 (6)output	5.76	L21-20	BA	10'	0U	5-20 (24), L6-20 (6)	2.3	68	2.0
PW107BA0U073	3	PW ePDU 6.7kW 2 x L6-20 input and IEC320-C13 (2 x 22)output	6.66	2 x L6-20	BA	10'	0U	IEC320-C13 (2 x 22)	2.4	68	2.0
PW309BA0U074	3	PW ePDU 8.6kW L21-30 input and IEC320-C19 (9), IEC320-C13 (24)output	8.65	L21-30	BA	10'	0U	IEC320-C19 (9), IEC320-C13 (24)	2.3	68	2.0
PW309BA0U075	2	PW ePDU 8.6kW L21-30 input and IEC320-C19 (3), IEC320-C13 (24), 5-20(6)output	8.65	L21-30	BA	10'	0U	IEC320-C19 (3), IEC320-C13 (24), 5-20(6)	2.3	68	2.0
PW309BA0U076	3	PW ePDU 8.6kW L21-30 input and IEC320-C13 (42)output	8.65	L21-30	BA	10'	0U	IEC320-C13 (42)	1.75	68	1.9
PW309BA0U077	2	PW ePDU 8.6kW L21-30 input and IEC320-C13 (30), 5-20 (6)output	8.65	L21-30	BA	10'	0U	IEC320-C13 (30), 5-20 (6)	1.75	68	1.9
PW110BA0U084	2	PW ePDU 10kW 2 x L6-30 input and IEC320-C13 (2 x 24)output	9.98	2 x L6-30	BA	10'	0U	IEC320-C13 (2 x 24)	3.2	64	1.9

Horizontal mount models

103004538-6501	2	PW ePDU 1.4kW 5-15 input and 5-15 (10)output	1.44	5-15	BA	12'	1U	5-15 (10)	17.5	1U	4.0
103004552-6501	2	PW ePDU 5kW Hardwired input and IEC320-C19 (2), IEC320-C13 (6)output	4.99	Hardwired	BA	NA	1U	IEC320-C19 (2), IEC320-C13 (6)	17.5	1U	4.0
103004548-6501	2	PW ePDU 2.5kW IEC320-C14 input and IEC320-C13 (12)output	2.50	IEC320-C14	BA	12'	1U	IEC320-C13 (12)	17.5	1U	4.0
103004550-6501	2	PW ePDU 3.3kW IEC320-C20 input and IEC320-C19 (2), IEC320-C13 (8)output	3.33	IEC320-C20	BA	12'	1U	IEC320-C19 (2), IEC320-C13 (8)	17.5	1U	4.0
103004545-6501	1	PW ePDU 1.9kW L5-20 input and 5-20 (10)output	1.92	L5-20	BA	12'	1U	5-20 (10)	17.5	1U	4.0
103004546-6501	2	PW ePDU 3.8kW L5-30 input and 5-20 (4)output	3.84	L5-30	BA	12'	1U	5-20 (4)	17.5	1U	4.0
PW103BA1U004	2	PW ePDU 2.9kW L5-30 input and 5-20 (8), 5-20 (1)output	2.88	L5-30	BA	15'	1U	5-20 (8), 5-20 (1)	19	1U	4.3
PW103BA1U005	2	PW ePDU 2.9kW L5-30 input and 5-20 (16)output	2.88	L5-30	BA	15'	1U	5-20 (16)	19	1U	4.3
PW103BA1U006	3	PW ePDU 2.9kW L5-30 input and 5-20 (16)output	2.88	L5-30	BA	15'	1U	5-20 (16)	19	1U	4.3
103004547-6501	2	PW ePDU 3.3kW L6-20 input and IEC320-C13 (12)output	3.33	L6-20	BA	12'	1U	IEC320-C13 (12)	17.5	1U	4.0
103004540-6501	2	PW ePDU 5kW L6-30 input and IEC320-C19 (2), IEC320-C13 (6)output	4.99	L6-30	BA	12'	1U	IEC320-C19 (2), IEC320-C13 (6)	17.5	1U	4.0
103004554-6501	2	PW ePDU 5kW L6-30 input and IEC320-C19 (2), IEC320-C19 (2)output	4.99	L6-30	BA	12'	1U	IEC320-C19 (2), IEC320-C19 (2)	17.5	1U	4.0
PW105BA1U045	2	PW ePDU 5kW L6-30 input and IEC320-C13 (20)output	4.99	L6-30	BA	15'	1U	IEC320-C13 (20)	19	1U	4.3
PW105BA1U046	2	PW ePDU 5kW L6-30 input and 6-15 (14)output	4.99	L6-30	BA	15'	1U	6-15 (14)	19	1U	4.3
PW105BA1U047	3	PW ePDU 5kW L6-30 input and IEC320-C13 (10)output	4.99	L6-30	BA	15'	1U	IEC320-C13 (10)	19	1U	4.3
103004551-6501	2	PW ePDU 5kW L14-30 input and 5-20 (4), L5-20 (2), L6-30(2)output	4.99	L14-30	BA	12'	2U	5-20 (4), L5-20 (2), L6-30(2)	17.5	2U	4.0
103004549-6501	2	PW ePDU 3.3kW L6-20 input and L6-20 (3)output	3.33	L6-20	BA	12'	2U	L6-20 (3)	17.5	2U	4.0
103004541-6501	2	PW ePDU 5kW L6-30 input and L6-20 (2), 6-20 (4)output	4.99	L6-30	BA	12'	2U	L6-20 (2), 6-20 (4)	17.5	2U	4.0

*Inventory Column

Indicates the stocking priority status. Items categorized as 1 have the highest priority in inventory stocking and replenishment. These are part of the Topseller program and should never be out of stock. Items categorized as 2 and 3 have respectively lower priorities.



PowerChain Management®

UNITED STATES
8609 Six Forks Road
Raleigh, NC 27615 U.S.A.
Toll Free: 1.800.356.5794
or 919.872.3020

www.powerware.com

CANADA
Ontario: 416.798.0112
Toll Free: 1.800.461.9166

LATIN AMERICA
Argentina: 54.11.4343.6323
Brazil: 55.11.3616.8500
México: 52.55.9000.5252

EUROPE/MIDDLE EAST/AFRICA
Denmark: 45.3686.7910
Finland: 358.94.52.661
France: 33.1.6012.7400
Germany: 49.0.7841.604.0
Italy: 39.02.66.04.05.40
Norway: 47.23.03.65.50
Sweden: 46.8.598.940.00
United Kingdom: 44.1753.608.700

ASIA PACIFIC
Australia: 61.2.9693.9366
New Zealand: 64.0.3.343.3314
China: 86.21.6361.5599
HK/Korea/Taiwan: 852.2745.6682
India: 91.11.2649.9414 to 18
Singapore/SEA: 65.6825.1668

Eaton, Powerware, PowerChain Management and ePDU are trade names, trademarks, and/or service marks of Eaton Corporation or its subsidiaries and affiliates.

© 2008 Eaton Corporation
All Rights Reserved
Printed in USA
PDU08FXA
March 2008

EATON

Powerware