



Powerware

Powerware® Monitored ePDU™

Product Focus



Features

- **High-density configurations** reduce enclosure space requirement
- **Fuse-less design** significantly reduces reset time
- **UL Listed (UL489) branch circuit breakers** meet UL60950-1 Edition requirements
- **Easy-Read digital ammeter** reduces local monitoring time (auto-scroll capability)
- **True RMS ammeter** provides accurate power measurement
- **Multi-purpose mounting** improves installation flexibility
- **Isolation hardware** improves product grounding
- **High-grade components** increases product reliability and fault-tolerance
- **Clearly labeled circuits** simplify load balancing

Designed for high-density, mission critical server applications provides maximum power for both standard and blade servers. Employing multiple configurations, the Easy-Read digital ammeter and remote power management with clearly labeled circuits, the ePDU assures easy management and monitoring for current requirements and future expansion.

Technical specifications

Part number	Inventory*	Description	Max kW	Input plug	Function	Serial	Ethernet	Local display	Cord	Orientation	Receptacles	Dimensions W H D		
Vertical mount 0U models														
PW102M00U031	1	PW ePDU 1.9kW L5-20 input and 5-20 (24)output	1.92	L5-20	MO	x		x	15'	0U	5-20 (24)	2.1	60	1.3
PW103M00U036	3	PW ePDU 2.9kW L5-30 input and 5-20 (24)output	2.88	L5-30	MO	x		x	15'	0U	5-20 (24)	2.1	60	1.3
PW104M00U044	2	PW ePDU 3.8kW 2 x L5-20 input and 5-20 (2 x 12)output	3.84	2 x L5-20	MO	x		x	15'	0U	5-20 (2 x 12)	2.1	60	1.3
PW105M10U096	2	PW ePDU 5kW L6-30 input and IEC320-C13 (24), IEC320-C19 (4)output	4.99	L6-30	MI		x	x	10'	0U	IEC320-C13 (24), IEC320-C19 (4)	2.3	60	2
PW105M10U097	2	PW ePDU 5kW L14-30 input and IEC320-C13 (20), 5-20 (4)output	4.99	L14-30	MI		x	x	10'	0U	IEC320-C13 (20), 5-20 (4)	2.3	64	2
PW105M10U098	2	PW ePDU 5kW L14-30 input and 5-20 (24)output	4.99	L14-30	MI		x	x	10'	0U	5-20 (24)	2.3	64	2
PW105M10U099	2	PW ePDU 5kW L14-30 input and IEC320-C13 (24), IEC320-C19 (2), 5-20(4)output	4.99	L14-30	MI		x	x	10'	0U	IEC320-C13 (24), IEC320-C19 (2), 5-20(4)	2.3	64	2
PW105M00U059	1	PW ePDU 5kW L6-30 input and IEC320-C13 (24)output	4.99	L6-30	MO	x		x	10'	0U	IEC320-C13 (24)	2.3	68	2.0
PW105M00U060	2	PW ePDU 5kW L6-30 input and IEC320-C19 (4), IEC320-C13 (24)output	4.99	L6-30	MO	x		x	10'	0U	IEC320-C19 (4), IEC320-C13 (24)	2.3	68	2.0

Technical specifications (cont.)

Part number	Inventory*	Description	Max kW	Input plug	Function	Serial	Ethernet	Local display	Cord	Orientation	Receptacles	Dimensions		
												W	H	D
PW105M00U061	2	PW ePDU 5kW L14-30 input and IEC320-C13 (20), 5-20 (4)output	4.99	L14-30	MO	x		x	10'	0U	IEC320-C13 (20), 5-20 (4)	2.3	64	2.0
PW105M00U062	2	PW ePDU 5kW L14-30 input and 5-20 (24)output	4.99	L14-30	MO	x		x	10'	0U	5-20 (24)	2.3	68	2.0
PW105M00U063	2	PW ePDU 5kW L14-30 input and IEC320-C19 (2), IEC320-C13 (24), 5-20(4)output	4.99	L14-30	MO	x		x	10'	0U	IEC320-C19 (2), IEC320-C13 (24), 5-20(4)	3.2	68	1.9
PW306MI0U113	1	PW ePDU 5.8kW L21-20 input and IEC320-C13 (24), IEC320-C19 (3), 5-20(6)output	5.76	L21-20	MI		x	x	10'	0U	IEC320-C13 (24), IEC320-C19 (3), 5-20(6)	2.3	68	2
PW306M00U071	1	PW ePDU 5.8kW L21-20 input and IEC320-C19 (3), IEC320-C13 (24), 5-20(6)output	5.76	L21-20	MO	x		x	10'	0U	IEC320-C19 (3), IEC320-C13 (24), 5-20(6)	2.3	68	2.0
PW306M00U072	2	PW ePDU 5.8kW L21-20 input and 5-20 (30)output	5.76	L21-20	MO	x		x	10'	0U	5-20 (30)	1.75	68	1.9
PW309MI0U114	1	PW ePDU 8.6kW L21-30 input and IEC320-C13 (24), IEC320-C19 (9)output	8.65	L21-30	MI		x	x	10'	0U	IEC320-C13 (24), IEC320-C19 (9)	2.3	68	2
PW309MI0U115	1	PW ePDU 8.6kW L21-30 input and IEC320-C13 (24), IEC320-C19 (3), 5-20(6)output	8.65	L21-30	MI		x	x	10'	0U	IEC320-C13 (24), IEC320-C19 (3), 5-20(6)	2.3	68	2
PW309M00U078	3	PW ePDU 8.6kW L21-30 input and IEC320-C13 (42)output	8.65	L21-30	MO	x		x	10'	0U	IEC320-C13 (42)	2.3	68	2.0
PW309M00U079	1	PW ePDU 8.6kW L21-30 input and IEC320-C19 (9), IEC320-C13 (24)output	8.65	L21-30	MO	x		x	10'	0U	IEC320-C19 (9), IEC320-C13 (24)	2.3	68	2.0
PW309M00U080	3	PW ePDU 8.6kW L21-30 input and IEC320-C13 (30), 5-20 (6)output	8.65	L21-30	MO	x		x	10'	0U	IEC320-C13 (30), 5-20 (6)	2.3	68	2.0
PW309M00U081	1	PW ePDU 8.6kW L21-30 input and IEC320-C19 (3), IEC320-C13 (24), 5-20(6)output	8.65	L21-30	MO	x		x	10'	0U	IEC320-C19 (3), IEC320-C13 (24), 5-20(6)	2.3	68	2.0
PW309M00U082	2	PW ePDU 8.6kW L21-30 input and IEC320-C13 (12), IEC320-C19 (15)output	8.65	L21-30	MO	x		x	10'	0U	IEC320-C13 (12), IEC320-C19 (15)	1.75	68	1.9
PW110MI0U116	2	PW ePDU 10kW IEC309-60 input and IEC320-C13 (30), IEC320-C19 (6)output	9.98	IEC309-60	MI		x	x	10'	0U	IEC320-C13 (30), IEC320-C19 (6)	2.3	70	2
PW110MI0U117	1	PW ePDU 10kW IEC309-60 input and IEC320-C13 (18), IEC320-C19 (9)output	9.98	IEC309-60	MI		x	x	10'	0U	IEC320-C13 (18), IEC320-C19 (9)	2.3	70	2
PW110MI0U118	1	PW ePDU 10kW IEC309-60 input and IEC320-C13 (42)output	9.98	IEC309-60	MI		x	x	10'	0U	IEC320-C13 (42)	2.3	70	2
PW110M00U087	2	PW ePDU 10kW IEC309-60 input and IEC320-C19 (9), IEC320-C13 (18)output	9.98	IEC309-60	MO	x		x	10'	0U	IEC320-C19 (9), IEC320-C13 (18)	2.4	70	2
PW110M00U088	2	PW ePDU 10kW IEC309-60 input and IEC320-C19 (6), IEC320-C13 (30)output	9.98	IEC309-60	MO	x		x	10'	0U	IEC320-C19 (6), IEC320-C13 (30)	2.3	70	2.0
PW110M00U089	2	PW ePDU 10kW IEC309-60 input and IEC320-C19 (12), IEC320-C13 (12)output	9.98	IEC309-60	MO	x		x	10'	0U	IEC320-C19 (12), IEC320-C13 (12)	2.3	70	2.0
PW110M00U090	2	PW ePDU 10kW IEC309-60 input and IEC320-C13 (42)output	9.98	IEC309-60	MO	x		x	10'	0U	IEC320-C13 (42)	2.3	70	2.0
PW323M00U095	3	PW ePDU 23kW hardwired input and C19 (12), C13 (2)output	23	hardwired	MO	x		x	NA	0U	C19 (12), C13 (2)	4	63	4
Horizontal mount models														
PW309M02U119	3	PW ePDU 8.6kW L21-30 input and IEC320-C13 (18), IEC320-C19 (3)output	8.65	L21-30	MO	x		x	10'	2U	IEC320-C13 (18), IEC320-C19 (3)	19	2U	18
PW317MI2U141	1	PW ePDU 17.3kW IEC309-60 input and IEC320-C19 (12)output	17.29	IEC309-60	MI	x	x	x	10'	2U	IEC320-C19 (12)	19	2U	17

*Inventory Column

Indicates the stocking priority status. Items categorized as 1 have the highest priority in inventory stocking and replenishment. These are part of the Topseller program and should never be out of stock. Items categorized as 2 and 3 have respectively lower priorities.



PowerChain Management®

UNITED STATES
8609 Six Forks Road
Raleigh, NC 27615 U.S.A.
Toll Free: 1.800.356.5794
or 919.872.3020

www.powerware.com

CANADA
Ontario: 416.798.0112
Toll Free: 1.800.461.9166

LATIN AMERICA
Argentina: 54.11.4343.6323
Brazil: 55.11.3616.8500
México: 52.55.9000.5252

EUROPE/MIDDLE EAST/AFRICA
Denmark: 45.3686.7910
Finland: 358.94.52.661
France: 33.1.6012.7400
Germany: 49.0.7841.604.0
Italy: 39.02.66.04.05.40
Norway: 47.23.03.65.50
Sweden: 46.8.598.940.00
United Kingdom: 44.1753.608.700

ASIA PACIFIC
Australia: 61.2.9693.9366
New Zealand: 64.0.3.343.3314
China: 86.21.6361.5599
HK/Korea/Taiwan: 852.2745.6682
India: 91.11.2649.9414 to 18
Singapore/SEA: 65.6825.1668

Eaton, Powerware, PowerChain Management and ePDU are trade names, trademarks, and/or service marks of Eaton Corporation or its subsidiaries and affiliates.

© 2008 Eaton Corporation
All Rights Reserved
Printed in USA
PDU11FXA
March 2008

