

EATON

Powerware

Powerware® Switched ePDU™

Product Focus



Features

- Encrypted password protection
- IP addressable outlet control
- Control power via web browser, telnet, serial, SNMP
- 100-240 volt operation, 20-30 amp input circuit
- Up to 24 individual On/Off/Reboot outlet control
- Outlet grouping and naming
- Current and voltage monitoring
- E-mail alerts of events
- Environmental monitoring
- Highly customizable firmware interface allowing for unit naming, outlet naming, sensor naming, multiple user login/passwords, individual receptacle control, automatic scheduling outlet on/off events, DHCP, secure web sever and password protection
- Environmental monitoring provides contact closure (door/water) sensors, temperature and humidity monitoring, over/under voltage, current or outlet status changes.
- Industrial grade design made of high quality components with multiple mounting options for flexibility

Designed for data centers, remote site management, the switched ePDU provides remote power monitoring of both voltage and current. The current is also displayed on a local two-digit current meter. Employing multiple configurations, available in 42" or 70" vertical lengths, providing individual on/off/reboot control of 8 to 24 AC power receptacles. The control interface is highly customizable with multiple functions and flexibility, allowing setup to send either SNMP traps or e-mail alerts.

Technical specifications

Part number	Inventory*	Description	Max kW	Input plug	Function	Serial	Ethernet	Local display	Cord	Orientation	Receptacles	Dimensions W H D		
Vertical mount 0U models														
PW306SW0U157	2	PW ePDU 5.8kW L15-20 input and IEC320-C13 (24)output	5.76	L15-20	SW	x	x	x	9'	0U	IEC320-C13 (24)	1.89	70	2
PW306SW0U155	2	PW ePDU 5.8kW L21-20 input and 5-15 (24)output	5.76	L21-20	SW	x	x	x	9'	0U	5-15 (24)	1.89	70	2
PW306SW0U156	1	PW ePDU 5.8kW L21-20 input and IEC320-C13 (24)output	5.76	L21-20	SW	x	x	x	9'	0U	IEC320-C13 (24)	1.89	70	2
PW102SW0U150	2	PW ePDU 1.9kW L5-20 input and 5-15 (8)output	1.92	L5-20	SW	x	x	x	9'	0U	5-15 (8)	1.89	42	2
PW102SW0U151	1	PW ePDU 1.9kW L5-20 input and 5-15 (24)output	1.92	L5-20	SW	x	x	x	9'	0U	5-15 (24)	1.89	70	2
PW103SW0U152	2	PW ePDU 2.9kW L5-30 input and 5-15 (16)output	2.88	L5-30	SW	x	x	x	9'	0U	5-15 (16)	1.89	70	2
PW103SW0U153	2	PW ePDU 3.3kW L6-20 input and IEC320-C13 (24)output	3.33	L6-20	SW	x	x	x	10'	0U	IEC320-C13 (24)	1.89	70	2
PW105SW0U154	1	PW ePDU 5kW L6-30 input and IEC320-C13 (16)output	4.99	L6-30	SW	x	x	x	9'	0U	IEC320-C13 (16)	1.89	70	2

***Inventory Column**

Indicates the stocking priority status. Items categorized as 1 have the highest priority in inventory stocking and replenishment. These are part of the Topseller program and should never be out of stock. Items categorized as 2 and 3 have respectively lower priorities.



PowerChain Management®

UNITED STATES
8609 Six Forks Road
Raleigh, NC 27615 U.S.A.
Toll Free: 1.800.356.5794
or 919.872.3020

www.powerware.com

CANADA
Ontario: 416.798.0112
Toll Free: 1.800.461.9166

LATIN AMERICA
Argentina: 54.11.4343.6323
Brazil: 55.11.3616.8500
México: 52.55.9000.5252

EUROPE/MIDDLE EAST/AFRICA
Denmark: 45.3686.7910
Finland: 358.94.52.661
France: 33.1.6012.7400
Germany: 49.0.7841.604.0
Italy: 39.02.66.04.05.40
Norway: 47.23.03.65.50
Sweden: 46.8.598.940.00
United Kingdom: 44.1753.608.700

ASIA PACIFIC
Australia: 61.2.9693.9366
New Zealand: 64.0.3.343.3314
China: 86.21.6361.5599
HK/Korea/Taiwan: 852.2745.6682
India: 91.11.2649.9414 to 18
Singapore/SEA: 65.6825.1668

Eaton, Powerware, PowerChain Management and ePDU are trade names, trademarks, and/or service marks of Eaton Corporation or its subsidiaries and affiliates.



© 2008 Eaton Corporation
All Rights Reserved
Printed in USA
PDU12FXA
March 2008